Main Specifications

MX6240N/ MX7040N	Base models include LCD, 150-sheet DSPF, 3000-sheet paper capacity (two tandem 2000-sheet trays/two 500 sheet trays), 1-TB hard disk drive, PCL6/Adobe® PostScript® 3™ network printing, colour network scanning, web browser, retractable keyboard and MXAMX2 application communication module
Type	Console, colour multi-function digital document system
Display	10.1" (diagonally measured) colour dot matrix high-resolution touch panel tilting display. 1024 x 600 dots (W-SVGA)
Functions	Copy, print, network print, network scan, document filing and fax[1]
Copy System	Dry electrostatic transfer/Dual component developer/Magnetic brush development/OPC drums/Belt type fusing/white LED exposure
Originals	Sheets and bound documents
Max Original Size	11" x 17"
Copy Size	Min. 5.5" x 8.5", Max. 11" x 17" + 12" x 18"
Copy Speed	62/70 ppm B&W/Colour (8.5" x 11")
Multiple Copy	Max. 9999 copies

First Copy Time (in Seconds)[2]	MX6240N		MX7040N	
	B&W	Colour	B&W	Colour
Platen Glass	4.0	5.6	3.7	5.1
DSPF	6.5	9.2	6.3	8.8

Warm Up Time	55 seconds or less[2]
Magnification	25% to 400% in 1% increments (with document feeder 25%-200%)
Original Feed	150-sheet DSPF
Scan Speed	DSPF Scan: Up to 150 IPM[2] (Monochrome); Up to 150 IPM[2] (Colour)
Original Sizes	5.5 x 8.5", 8.5" x 11", 8.5" x 11" R, 8.5" x 14", 11" x 17"
Paper Capacity	Std. 3000 Sheets/Max. 8500 Sheets
Paper Feed Sizes	Standard: Tandem Tray 1 - 1200 sheets (letter size), Tandem Tray 2 - 800 sheets (letter size), Trays 3/4 - 500 sheets ea. (letter/legal/ledger/statement/12" x 18"). Optional: Multi-bypass Tray (for machine) - 100 sheets (letter/legal/ ledger/statement/monarch or COM10 envelopes/12" x 18"), Multi-bypass (for LCT) - 500 sheets (letter/legal/ ledger/statement/12" x 18"), LCT (2-Drawer) - 2500-sheets each drawer (letter/legal/ledger/12" x 18"), Letter LCC - 3500 sheets (letter), Ledger LCC: 3000 sheets (letter/legal/ledger).
Paper Weights and Types	Tandem Trays - 16-28 lb. bond, Trays 3/4 - 16 lb. bond to 100 lb. bristol, Multi-bypass Tray (for machine) - 15 lb. bond to 110 lb. cover, Multi-bypass Tray (for LCT) - 15 lb. bond to 100 lb. bristol, LCT (2-drawer) - 15 lb. bond to 110 lb. cover, Letter LCC/Ledger LCC - 16 lb. bond to 100 bristol. Supported paper types include thin, plain, recycled, colour, letterhead, pre-printed and pre-punched, embossed and glossy.
Duplexing	Standard automatic duplex copying and printing
CPU	Up to 1.8 GHz Multi-Processor Controller
Interface	RJ-45 Ethernet (10/100/1000Base-T), USB 2.0 (2 host ports, front and rear), USB 2.0 (1 device port)
Memory	Standard 5 GB
Hard Disk Drive	1 TB
Copy Resolution	Scan: B&W/colour: 600 x 600 dpi; Copy: B&W/colour: 600 x 600 dpi
Colour Modes	Photo, Full Colour Mode, Monochrome (B/W)
Exposure Control	Modes: Text, Text/Photo, Text/Printed-Photo, Printed-Photo, Photo, Map, Pale-Colour. Settings: Auto or 9 step manual
Halftone	256 gradations/2 levels (monochrome)
Copy Features	Electronic sort, Auto Colour Sensing (ACS), Auto Paper Selection (APS), Auto Magnification Selection (AMS), image preview/edit, auto tray switching, rotate copy, reserve copy, tandem copy, book copy, margin shift, edge/centre erase, book divide, dual page, cover/insert page, OHP insert, job build, card shot, blank page skip, mirror/reverse, proof, pamphlet, watermark, custom image, job programs.
Account Control	Up to 1000 users. Supports user-number authentication (on device), login name/password or login name/password (via LDAP server) for Copy, Print, Scan, Fax and document management.
Output Tray Capacity	Main output tray (top) 250 sheets (face down)
Firmware Management	Flash ROM with local (USB), network update capability and firmware update 1 to N with SRDM (Sharp Remote Device Management)
Configuration Method	Web-based management with user/administrator level login, cloning (1 to N) with SRDM and remote front panel access
Service/Functions	Remote front panel, remote access to service logs and click counts
Accessibility Features	Tilt Front Panel, Adjustment of Key Touch-Send and Speed, Document Feeder Free Stop, Job Programs, Remote Front Panel, Universal Grip for Paper Trays, and Disable Screen Timeout
Environmental Standards	International Energy Star Program Ver. 1.1, Law on Promoting Green Purchasing. European RoHS (Restriction of Hazardous Substances)
Power Source	AC 208-240 VAC, 60 HZ, 20 Amps
Power Consumption	Maximum: 2880 W or less
Weight	MX6240N/7040N: Approx. 490 lbs.
Approx. Dimensions	33.25" (w) x 33.25" (d) x 48" (h)

Network Printing System (Standard)

PDL	Standard PCL® 6 compatible Adobe®, PostScript® 3™, optional XPS
Resolution	1200 x 1200 dpi/8-bit processing
Print Speed	62/70 pages per minute (8.5" x 11")
Print Drivers	Windows Server® 2003-2008, Windows XP, Windows XP x64, Windows Server 2003-2008 x64, Windows Vista®, Windows Vista® x64, Windows 7, Windows 7 x64, MAC OSX (including 10.4.11, 10.5-10.5.8, 10.6.5-10.6.8, 10.7-10.7.2), all MAC PPD.
Features	Auto configuration, continuous printing, electronic sorting, N-up printing, duplex printing, transparency inserts, margin shift, image rotation, different cover page, poster print, job bypass print, job retention, confidential print, proof print, user authentication, image stamp and watermarks. Additional features: Multiple pamphlet print, network tandem print, carbon copy print mode, different cover page/last page/other page, form overlay, tab paper settings, tab printing, chapter inserts and page Interleave[1]
Direct Printing	File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Encrypted PDF, PostScript and Windows XPS[1] (FTP, Web page, E-mail and USB)
Resident Fonts	80 outline fonts (PCL), 136 fonts (PS)
Interface	RJ-45 Ethernet 10/100/1000Base-T, USB 2.0
Operating Systems	Windows Server 2003-2008, Windows XP, Windows Vista, Windows 7, MAC OS 9-9.2.2, MAC OSX 10.2.8, 10.3.9, 10.4.11, 10.5-10.5.8, 10.6-10.6.5, Novell® Netware® 3x, 4x, 5x, Sun® OS 4.1x, Solaris® 2x, Unix®, Linux® and Citrix® (Metaframe, Presentation Server 4, 4.5) and Windows Terminal Services.[1]
Network Protocols	TCP/IP (IPv4, IPv6, IPSEC) SSL (HTTP, IPP, FTP), SNMPv3, SMTP, POP3, LDAP, 802.1x for Windows and Unix. LPD and LPR for Unix. IPX/SPX® for Novell environments and EtherTalk®. AppleTalk® for Macintosh® environments.[1]
Printing Protocols	LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP and Novell Pserver/Rprinter
Network Security	IP/MAC address filtering, protocol filtering, port management, user authentication and document administration.[1]
Security Standards	IEEE-2600™-2008, DoD (NSTISSP) #11, DoD Directive 8500.2, DoD (DISA)

Network Scanning System (Standard)

Scan Modes	Standard: Colour, monochrome, greyscale
Max. Original Size	11" x 17"
Optical Resolution	600 dpi
Output Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
Image Formats	Monochrome: TIFF, PDF, Encrypted PDF, XPS Colour: Greyscale, Colour TIFF, JPEG, PDF, Encrypted PDF, XPS Internet Fax: TIFF-FX, TIFF-F, TIFF-S[1]
Image Compression	Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR) Colour/Greyscale: JPEG (high, middle, low)
Scan Destinations	Internet Fax mode: MH/MMR (option); E-mail, Desktop, FTP, Folder (SMB), USB, Internet fax (option); Super G3 fax (option)
One-touch Dest.	Up to 2000 (combined scan destinations)
Group Destinations	Up to 500
Programs	48 (combined)
Max. Jobs	Up to 100
Network Protocols	TCP/IP and SSL (includes HTTP, SMTP, LDAP, FTP, POP3), SMB, ESMTP and 802.1x.
Network Security	E-mail server user authentication for LDAP and Active Directory
Software	Sharpdesk® desktop personal document management software (1 user license included)
Sharp OSA Platform	Application Communication Module (MXAMX2) standard

Inserter (MXCF11 Option)

Type	Standing, 2 Trays
Paper Capacity	Upper Tray: 200 Sheets; Lower Tray: 200 Sheets (20 lb. bond)
Paper Weight	16 lb. bond to 100 lb. Bristol (Paper feeding)
Paper Size	Up to 12" x 18"
Power Consumption	70 W or Less
Power Source	24 Volts (Supplied by Main Unit)
Dimensions	21.5" (w) x 30" (d) x 50.5" (h)
Weight	Approx. 51 lbs.

Multi-Folding Unit (MXFD10 Option)

Type	Floor Standing
Dimensions	13.5" (w) x 30.5" (d) x 41.5" (h)
Weight	Approx. 146 lbs.
Power Source	Powered by MXFN21/FN22 Finisher
Power Consumption	Maximum: Standby: 23 W or less; In Operation: 150 W or less
Folding Mode	Z-fold, 3-fold inside, 3-fold outside, 4-fold, 2-fold

4K 100-Sheet Stapler/Finisher (MXFN21: option)

Type	4000-sheet console stapler finisher (100-sheet stapling)
Output Trays	Upper tray: Moving offset tray (up to 1500 letter size sheets) Middle tray: 250 sheets (letter size, non-stapled) Lower tray: Moving offset tray (up to 2450 letter size sheets)
Stapling Capacity	Up to 100 sheets (letter/statement)
Stapling Media	Plain paper, letter/legal/ledger size or mixed
Stapling Positions	1 front, 1 rear, or 2 point stitching
Hole Punching	Optional three-hole punch unit MXPN13B
Power Source	120 VAC, 60 HZ, 15 Amps
Power Consumption	220 W/350 W with MXMF10
Weight	Approx.: 134.5 lbs.
Dimensions	Approx.: 30.75" (w) x 30" (d) x 41" (h) (with tray extended)

4K 100-Sheet Stapler/Saddle Stitch Finisher (MXFN22: option)

Type	4000-sheet console stapler finisher (100-sheet stapling)
Output Trays	Upper tray: Moving offset tray (up to 1500 letter size sheets) Middle tray: 250 sheets (letter size, non-stapled) Lower tray: Moving offset tray (up to 2450 letter size sheets)
Stapling Capacity	Up to 100 sheets (letter/statement)
Stapling Media	Plain paper, letter/legal/ledger size or mixed
Stapling Positions	1 front, 1 rear, or 2 point stitching
Saddle Stitch	Centre stitch/centre fold (2 staples) letter/legal/ledger paper sizes
Saddle Stitch	Up to 5 sets (16-20 sheets)/10 sets (11-15 sheets per set)/15 sets (6-10 sheets per set)/25 sets (1-5 sheets per set)
Max. Sets	15 sets (6-10 sheets per set)/25 sets (1-5 sheets per set)
Hole Punching	Optional three-hole punch unit MXPN13B
Power Source	120 VAC, 60 HZ, 15 Amps
Power Consumption	220 W/350 W with MXMF10
Weight	Approx.: 134.5 lbs.
Dimensions	Approx.: 30.75" (w) x 30" (d) x 41" (h) (with tray extended)

Optional Equipment

MXLC12	3500-sheet Large Capacity Cassette (letter)[1]
MXLC13	5000-sheet Large Capacity 2-Drawer Air Feed Tray (ledger)[1]
MXLCX3N	3000-sheet Large Capacity Cassette (ledger)[1]
MXMF10	100-sheet Multi-bypass Tray (for machine)
MXMF11	500-sheet Multi-bypass Tray (for MXLC13)
MXFN19	4K Stacking 50-Sheet Staple Finisher[1]
MXFN20	4K Stacking 50-Sheet Staple/Saddle Stitch Finisher[1]
MXFN21	4K Stacking 100-Sheet Staple Finisher[1]
MXFN22	4K Stacking 100-Sheet Staple/Saddle Stitch Finisher[1]
MXCF11	2-Tray Inserter Unit[1]
MXFD10	Multi-folding Unit[1]
MXRB12	Paper Pass Unit (for machine)
MXRB13	Relay Unit[1]
MXRB14	Paper Pass Unit (for MXLC13)
MXRB15	Curl Correction Unit[1]
MXTM10	Trimmer Unit[1]
MXPN12B	3-Hole Punch Unit (for MXFN19/FN20)
MXPN13B	3-Hole Punch Unit (for MXFN21/FN22)
ARSC2	Staple Cartridge (for MXFN19/FN20)
ARSC3	Staple Cartridge (for MXFN20)
MXSCX1	Staple Cartridge (for MXFN20)
MXSCX2	Staple Cartridge (for MXFN21/FN22)
MXTR14	Right Side Exit Tray
MXTU14	Centre Exit Tray
ARSU1	Stamp Unit (requires ARSV1 Stamp Cartridge)
ARSV1	Stamp Cartridge (required for ARSU1)
MXPF10	Bar Code Font Kit
MXPUX1	XPS Expansion Kit
MXEB11	Enhanced Compression Kit
MXFX11	Fax Expansion Kit
MXFWX1	Internet Fax Expansion Kit
MXEB15	HDD Mirroring Expansion Kit
MXFR36U	Commercial Data Security Kit
MXAMX1	Application Integration Module
MXAMX3	External Accounting Module

Supplies

MX62NTBA	Black Toner Cartridge
MX62NTCA	Cyan Toner Cartridge
MX62NTMA	Magenta Toner Cartridge
MX62NTYA	Yellow Toner Cartridge
MX62NVBA	Black Developer
MX62NVSA	Cyan/Magenta/Yellow Developer
MX62NRSA	Drum
MX700HB	Toner Collection Container

[1] Some features require optional equipment and/or software.
[2] Specification may vary depending on product configuration, machine settings and operating conditions.

Colour Consistency System

OSA® Sharp Open Systems Architecture

ImageSEND

mV™ SHARP

energy ENERGY STAR

the SHARP experience   see what happens   **SHARP**